

WILDEN PUMP DESIGNATION SYSTEM

**P.025 ORIGINAL™
 PLASTIC**

**6 mm (1/4") Pump
 Maximum Flow Rate:
 18.2 lpm (4.8 gpm)**

LEGEND

P.025 / XXXXX / XXX / XX / XXX / XXXX

MODEL

WETTED PARTS & OUTER PISTON

CENTER SECTION

AIR VALVE

DIAPHRAGMS

VALVE BALLS

O-RINGS

VALVE SEAT

SPECIALTY
 CODE
 (if applicable)

MATERIAL CODES

WETTED PARTS & OUTER PISTON

KK = PVDF / PVDF
 KZ = PVDF / NO PISTON
 PP = POLYPROPYLENE /
 POLYPROPYLENE
 PZ = POLYPROPYLENE /
 NO PISTON

CENTER SECTION

LL = ACETAL
 PP = POLYPROPYLENE

AIR VALVE

L = ACETAL
 P = POLYPROPYLENE

DIAPHRAGMS

BNS = BUNA-N (Red Dot)
 TNL = PTFE W/ NEOPRENE
 BACK-UP O-RING,
 IPD (White)
 WFS = WIL-FLEX™ [Santoprene®
 (Orange Dot)]

VALVE BALL

TF = PTFE (White)

VALVE SEAT

K = PVDF
 P = POLYPROPYLENE

VALVE SEAT O-RING

BN = BUNA-N (Red Dot)
 TV = PTFE ENCAP. VITON®
 WF = WIL-FLEX™ [Santoprene®]

SPECIALTY CODES

0502 PFA coated hardware
 0512 Adapter block, no muffler, Pro-Flo®,
 center section

Viton® is a registered trademark of Dupont Dow Elastomers.