



## Applications

### NON-CORROSIVE, INDUSTRIAL LIQUIDS:

- Fuel Oils
- Lube Oils
- Jet Fuels
- Gasoline
- Edible Oils

### SOLVENTS & THINNERS:

- Esters
- Ketones
- Naphthas
- Ethers
- Amines
- Aromatics
- Alcohols
- Terpenes
- Glycols

### SERVICES:

- Batch Blending
- Loading & Unloading
- Pressure Boosting Stations
- Priming Systems
- Aviation Fuel Skids
- Portable Transfer Skids

## GNX Series PERFORMANCE & SPECIFICATIONS

### Maximum Operating Limits

Pump Model	Nominal Flow Rate Range	Viscosity	Maximum Operating Temperature	Min./Max. Speed	Maximum Working Pressure	Maximum Differential Pressure
GNX2, GNXH2	7 - 86 gpm (26 - 325 L/min)	0.2 - 4,250 cP	-25°F to 300°F (-32°C to 149°C)	200 - 814 rpm	175 psi (12.1 bar)	125 psi (8.6 bar)
GNX2.5, GNXH2.5	12 - 155 gpm (45 - 587 L/min)	0.2 - 4,250 cP	-25°F to 300°F (-32°C to 149°C)	200 - 814 rpm	175 psi (12.1 bar)	125 psi (8.6 bar)
GNX3, GNXH3	100 - 275 gpm (379 - 1,041 L/min)	0.2 - 4,250 cP	-25°F to 300°F (-32°C to 149°C)	200 - 700 rpm	175 psi (12.1 bar)	100 psi (6.9 bar)
GNX4, GNXH4	250 - 500 gpm (946 - 1,893 L/min)	0.2 - 4,250 cP	-25°F to 300°F (-32°C to 149°C)	200 - 563 rpm	175 psi (12.1 bar)	100 psi (6.9 bar)